



Infinity II & Infinity II RFID in-room safes

The unmatched in-room safe

Infinity II series, a new era in hotel in-room safes. Infinity II is ideal for the most demanding hotels, lifestyle brands and boutique properties that thrive to be different. By combining sophisticated technology and fashionable design, Infinity II is the ultimate safe for the design conscious hotelier.

With the silky, stylized design and high tech neon blue backlit keypad (digital only), combined with Elsafe's industry leading high quality safe platform, Infinity II brings richness to the hotel room like no other safe before.



UL-1037

FEATURES:

Infinity II Series

- UL-1037 Certified for physical strength and security.
- Industry-leading audit trail.
- Audit trail with in-room print-out option.
- Attractive, ergonomic design.
- Revolutionary locking system with interlocking deadbolt mechanism.
- One piece, cold-pressed curved door is over 70% stronger than flat steel door.
- Extended solid steel bolt hinges for maximum security and durability.
- Solid, arc-welded heavy-gauge steel construction and recessed back for superior strength and security.
- Anti-tamper switch.
- Powered with 5 LR6/AA batteries.
- Easy outside battery change.
- Spring loaded door.
- 3 size options in depth (25 / 41 / 49 cm).
- Laptop compatible up to 17".
- Compatible with SafeLink and PinKey PLUS.
- Flash memory.
- Unique modular construction for easy upgrade ability.
- Optional inside light.
- Inside carpet.
- Internal power outlet options (EURO/UK/US) on inside of door for guest convenience.
- Main power option.
- Confirmation buzzer.


Infinity II Digital

- ADA compliant telephone keypad.
- 4- or 6- digit guest code.
- High tech neon blue backlit display for clear visible numbers.
- Push button to lock door.
- RFID upgradable.

Infinity II RFID

- Compatible with Signature RFID by VingCard electronic lock, thus operating the same RFID guest room key.
- 13,56MHz technology.
- Compatible with the following standards:
 - » ISO 14.443 A (MIFARE)
 - » ISO 14.443 B
 - » ISO 15.693
- Compatible with Near Field Communication (NFC) standards.





EXTENDED SOLID STEEL BOLT HINGES ARE SECURE AND

ULTRA-RELIABLE.

5.255 25, 11 d.1d 17 d.11 d.15 5.4511d.1				
Measurements		Infinity II 25	Infinity II 41	Infinity II 49
Outside H/W/D	mm	206/437/260 81/8/173/16/103/16	206/437/421	206/437/502
Incl. keyboard	in		8 ^{1/8} /17 ^{3/16} /16 ^{5/8}	81/8/173/16/913/16
Inside H/W/D	mm	196/428/168	196/428/330	196/428/411
	in	7 ^{11/16} /16 ^{13/16} /6 ^{9/16}	7 ^{11/16} /16 ^{13/16} /13	7 ^{11/16} /16 ^{13/16} /16 ^{3/16}
Door dimensions	mm	148/320	148/320	148/320
H/W	in	5 ^{13/16} /12 ^{5/8}	5 ^{13/16} /12 ^{5/8}	5 ^{13/16} /12 ^{5/8}
Internal volume	litres	14,1	27,7	34,5
	cu ft	0,50	0,98	1,22
Weight	kg	11,6	15,1	17,4
	Ib	23,8	33,3	38,4

H/W/D: Height/Width/Depth

	Standard Color	Color Option 2	Color Option 3
	101	0	0
Body color	Black	White	Black
Frame color	Glossy Black	Glossy White	Gold

• Override: SafeLink & PinKey PLUS

ELSAFE'S REVOLUTIONARY LOCKING SYSTEM RESISTS FORCIBLE ENTRY.

• Steel thickness: Door: 4 mm / Frame-Backwall: 2,5 mm / Body: 2 mm

Fastening method: Backwall: 2 bolts / Bottom: 4 holes



SafeLink:

Elsafe SafeLink helps you set up and service your Infinity II safe in seconds. With Infinity II by Elsafe you can even print a detailed 100-event log from the safe memory.

PinKey PLUS:

Elsafe PinKey Plus is a compact and powerful electronic PIN-code protected,



non-resident electronic key to securely override Elsafe in-room safes. This allows for easy day-to-day safe operations.

Infinity II - RF Online compatible:

Infinity II in-room safes are upgradeable with optional wireless RF-online communication (RF-online upgrade requires VISIONLINE by VingCard Zigbee RF-online network to be installed).



Outlets:

Optional internal power outlet mounted on the door for the guest's ease of use (EURO, US and UK).







The unmatched in-room safe.



InfinityI

VingCard Elsafe

ASSA ABLOY

VingCard Elsafe AS

x 511 • 1522 Moss • Norway

P.O. Box 511 • 1522 Moss • Norway
Tel: +47 69 24 50 00 • Fax: +47 69 24 50 50
E-mail: info@vcegroup.com • www.vcegroup.com